



# ADECO® FRIZANTIN® 100%

### **Description:**

ADECO® FRIZANTIN® 100% is a concentrated coolant of blue colour which is used in cooling systems of motor vehicles. It is produced on the basis of Monoethylene Glycol and a special additive package. Before use it must be diluted with water according to the table of dilution ratio.

### **Application:**

ADECO® FRIZANTIN® 100% protects the engine from overheating in summer and freezing in winter. It provides superior corrosion protection of all metal parts of the cooling system of motor vehicles. It is designed to fully meet the highest requirements for additional protection of all aluminium engine parts from corrosion. It can be also used in other open and closed cooling systems. The recommended drain period is two years. It can be mixed with other coolants produced on the same basis.

### **Performance Benefits:**

- Excellent protection against frost;
- Superior corrosion protection, especially of aluminium alloys;
- Excellent thermal properties;
- Long-term protection;
- No foaming tendency.

### **Physical and Chemical Characteristics:**

- Density at 20<sup>0</sup>C, g/cm<sup>3</sup> 1.15 - 1.17
- pH value 8.50
- Ash, % 0.45
- Colour blue

### **Dilution Ratio:**

<b>FRIZANTIN 100%: WATER (%v/v)</b>	<b>FREEZING POINT (°C)</b>
1.0 : 0.5	- 57
1.0 : 1.0	- 37
1.0 : 1.5	- 26
1.0 : 2.0	- 18
1.0 : 2,5	- 14
1.0 : 3.0	- 11
1.0 : 3.5	- 9
1.0 : 4.0	- 6



## Technical Data Sheet

---

**Meets the requirements of the following standards:**

SRPS H.Z2.010/ASTM D 3306 Type 1; BS 6580:1992 and AFNOR R15-601.

The quality is controlled by an accredited laboratory.

**Packages:**

12 x 1 lit., 12 x 1 kg, 60 lit. and 220 kg.