



# ADECO<sup>®</sup> FRIZANTIN<sup>®</sup> G12 -40

### Description:

ADECO<sup>®</sup> FRIZANTIN<sup>®</sup> G12 -40 is a prepared Monoethylene Glycol based coolant of fluorescent pink colour, designed for use in the latest generation of motor vehicles with cooling systems produced on the basis of aluminum and light metals, which is used without dilution with water.

### Application:

ADECO<sup>®</sup> FRIZANTIN<sup>®</sup> G12 -40 provides maximum protection from freezing in winter and from overheating in summer. It provides improved corrosion protection of all metal parts, especially aluminium ones, fittings, hoses, plastic parts of refrigerators, etc. It prevents formation of foam and lime deposits. It guarantees improved heat transfer, providing increased engine flexibility and maximum reliability to users. It is suitable for use in open and closed loop cooling systems. It does not contain any nitrites, amines, phosphates, borates or silicates. A special additive package provably provides extended coolant drain interval of at least five years or 650.000 km (8.000 hours of operation) in heavy off-road vehicles, 250.000 km (2.000 hours of operation) in passenger cars and light commercial vehicles, and 32.000 hours of operation (6 years) in stationary engines.

### Performance Benefits:

- Extended drain interval, at least 5 years;
- Limited loss of corrosion inhibitors - less than 10%, provides maximum corrosion protection of all parts of the engine and of the cooling system of the vehicle;
- Superior and maximum protection of aluminium and aluminium parts, fittings, hoses and plastic parts of refrigerators;
- New technology guarantees improved heat transfer;
- Extends the service life of the water pump by 50% on average;
- Provides maximum reliability to users.

### Physical and Chemical Characteristics:

	ADECO <sup>®</sup> FRIZANTIN <sup>®</sup> G12 -40
Nitrites, amines, phosphates, borates, silicates	None
Colour	pink fluorescent
Specific Gravity, 20°C	1.068 typ.
Boiling Point	109°C typ.
pH	8.85
Freezing Point	-38°C typ.



**Meets the requirements of the following standards:**

BS 6580; ASTM D3306/4985; AFNOR NF R15-601; VW/Audi/Seat/Škoda/Porsche TL 774-D/F(G12/G12+); Ford WSS M97B44-D/E; MB 325.3 i MAN 324 Type SNF.

The quality is controlled by an accredited laboratory.

**Packages:**

12 x 1 lit., 60 lit. and 220 kg.