

ADECO® FRIZANTIN® 100%

Product Description:

ADECO® FRIZANTIN® 100%, concentrated coolant for cooling systems of motor vehicles, based on monoethylene glycol and special additives packages. Before use it must be diluted with water according to the mixing table.

Purpose:

ADECO® FRIZANTIN® 100% Protects the motor from overheating in summer and freezing in winter. Provides excellent corrosion protection for all aluminium parts of the cooling system of motor vehicles. The recommended replacement period is 2 years or 50,000 km traveled. It can also be used in either open and closed cooling systems. It can be mixed with other coolants produced on the same basis.

The Main Advantages:

- Excellent freezing protection;
- Excellent protection against corrosion, especially aluminum alloys;
- Good thermal properties;
- Long-term protection;
- Does not create a foam.

Physical and Chemical Properties:

<i>Characteristic, Unit</i>	<i>Referential Values</i>	<i>Method</i>
Density at 20°C, g/cm ³	1,15 – 1,17	ASTM D 1122
pH valur	8 – 9	pH Indicator Strips
Ash, %	0,45	
Color	blue	Visual



Mixing table:

FRIZANTIN 100% : WATER (%v/v)	FREEZING POINT (°C)
1,0 : 0,5	- 57
1,0 : 1,0	- 37
1,0 : 1,5	- 26
1,0 : 2,0	- 18
1,0 : 2,5	- 14
1,0 : 3,0	- 11
1,0 : 3,5	- 9
1,0 : 4,0	- 6

Meet Specifications:

SRPS H.Z2.010 Tip 1; BS 6580; ASTM D 3306/4985 Tip 1; AFNOR NF R15-601;
VW/Audi/Seat/Škoda/Porsche TL 774-C (G11); MB 325.0; MAN 324 Type NF; BMW N600

Packaging: 1 kg, 1 L, 3 L, 60 L, 220 kg, 1000 L